

POS | LABEL | PORTABLE | PANEL | KIOSK



Swift & Easy Printing Solutions



STR870E

POS

PRINTER SOLUTIONS

>> Receipt Printer



Swift 80mm POS Printers



Advantages :

- Design for kitchen condition, water proof, oil proof
- Paper out front, suitable for various application scenarios
- Voice sound and light alarm, fast response to incoming orders
- Multiple interfaces - USB/Ethernet/Cash Drawer
- Paper shortage alarm, cover open alarm, over heated protection, voice sound indicator
- Auto cutter, free choice for full cut or partial cut

Application Scenarios :



Tax



Receipt



Retail



POS



Catering



Garment

STR870E

Professional Kitchens POS Receipt Printer

Print Method	Thermal line
Resolution	8dots/mm , 576dots/line
Print Speed	200mm/s
Effective Print Width	72mm
Paper Width	79.5mm±0.5mm
Self-defined Characters	Yes
Graphic Print	Support diagram and downloaded bitmap
Print Font	GB18030: 24×24 ASCII: 12×24
Barcode	1D:UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODABAR, CODE93, CODE128
	2D: PDF417, QRCODE, DataMatrix barcode Print
Interface	USB + Ethernet + Cash Drawer
Other Functions	Paper shortage alarm, Open cover alarm, Printer head overheating protection; Optional: voice broadcast
Cash Drawer	DC24V, 1A, 6-pin RJ-11 socket
Power Supply	DC24V±10%, 2A, DC005-2.5 power socket
Paper Type	Thermal paper 80×φ80mm (MAX)
Paper Thickness	0.06mm ~ 0.08mm
Paper Loading Method	Drop-in easy paper loading
Paper Cutting Method	Auto Cutter (full cut/partial cut, optional)
Dimension	179mm×140mm×138mm (L×W×H)
Weight	1120g (without paper roll)
Operation Temp/Humidity	0°C ~ 50°C/10% ~ 80%
Storage Temp/Humidity	-20°C ~ 60°C /10% ~ 90%
Print Head Life	150km
Cutter Life	1,500,000 cuts

